

GF/GX series

Quality, Speed and Economy

STOLZ
CO.,LTD.

Line Filter

GF For general resin		GF-10-001	GF-10-002	GF-20-001	GF-20-002	GF-20-003
Mounting location		On the supply line	On the hopper	On the supply line	On the hopper	On the supply line
Hose dia.	mm	25	25	38	38	38
Filter length	mm	155	155	252	252	252
Hight	mm	348	302 (on the hopper)	448	381 (on the hopper)	833 (included dust tank)
Weight	kg	2.9	2.9	3.3	3.6	9.5
Accessories		Antistatic hose (with dust collecting cap)				Dast tank (15L)

GF Magnetic separator installed		GF-15-001	GF-15-002	GF-25-001	GF-25-002	GF-25-003
Mounting location		On the supply line	On the hopper	On the supply line	On the hopper	On the supply line
Hose dia.	mm	25	25	38	38	38
Filter length	mm	155	155	252	252	252
Hight	mm	431	373 (on the hopper)	566	432 (on the hopper)	956 (included dust tank)
Weight	kg	4.6	4.6	5.6	6.7	14.6
Accessories		Antistatic hose (with dust collecting cap)				Dast tank (15L)

GX For transparence / optical resin		GX-10-002	GX-20-002
Mounting location		On the hopper	On the hopper
Hose dia.	mm	25	38
Filter length	mm	155	252
Hight	mm	307 (on the hopper)	386 (on the hopper)
Weight	kg	3.9	5.2
Accessories		Antistatic hose (with dust collecting cap)	

● Specifications are subject to change without notice.

STOLZ CO.,LTD.

Head Office ■ 2-3-10, Chuo, Murayama City, Yamagata Pref., 995-0035 Japan Tel: +81-237-53-3771 Fax: +81-237-53-3770 E-mail: stolz@stolz.co.jp Web Site: www.stolz.co.jp