

# DEZAT NX-N series

Quality, Speed and Economy

**STOLZ**  
CO.,LTD.

## Compact Optical Resin Dehumidifying Dryer with N<sub>2</sub> Gas Generator

			NX-3N	NX-5N
Compatible molding machines	tf		--50	--80
Drying capacity (in the PC use)	kg/h		1.0	1.6
Max. working temperature	°C		150	150
Loading capacity	L(kg)		5 (3)	8 (5)
Compressed air	Air pressure	MPa	0.7	0.7
	Air consumption	NL/min	90	90
N <sub>2</sub> gas supply rate (at 99.9% purity)	kVA		3.78 / 3.92	3.78 / 3.92
Power	Total electric capacity (50/60Hz)	kW	2.23 / 2.53	2.23 / 2.53
	Power consumption (50/60Hz)	kW	1.6	1.6
	Heater power	kW	0.08	0.08
	Dryer blower power (50/60Hz)	kW	0.55 / 0.85	0.55 / 0.85
	Supply blower power (50/60Hz)	NL/min	5.0	6.5
	Power supply standard		200 / 220V 50 / 60Hz 3ø	
	Power plug		20A-3P plug with protective ground	
Dryer outer dimensions (WxDxH)	mm		500 x 690 x 1,430	500 x 690 x 1,430
Dryer drum outer dimensions (øxH)	mm		280 x 410 x 900	280 x 410 x 1,020
Dryer weight	kg		118	118
Dryer drum weight	kg		24	27
Accessories	Antistatic hose		ø25mm x 4m x 1	
	Suction hose		ø25mm x 4m x 1	
	Silicone duct hose		ø38mm x 2m x 2	
	Suction nozzle		ø25mm x 1	

- Dryer drum outer dimensions and weight include the standard GX-10 hopper.
- Specifications are subject to change without notice.

**STOLZ CO.,LTD.**

Head Office ■ 2-3-10, Chuo, Murayama City, Yamagata Pref., 995-0035 Japan Tel: +81-237-53-3771 Fax: +81-237-53-3770 E-mail: stolz@stolz.co.jp Web Site: www.stolz.co.jp